


NEU2178GK



ENGINEERING CODE
9590A51



REFRIGERANT
R-404A



POWER SUPPLY
220-240 V 50 Hz



APPLICATION
LBP



MOTOR TYPE
CSCR



STANDARD
EN12900



COOLING CAPACITY
478 W



EFFICIENCY
1.1 W/W

DATA

GENERAL DATA

Model	NEU2178GK
Type	Hermetic Reciprocating
Technology	ON/OFF
Compressor Application	LBP
Expansion Device	Capillary Tube or Expansion Valve
Compressor Cooling	Fan/220
HP	1
Starting Torque	HST
Plant	SLOVAKIA

ELECTRICAL DATA

Start Winding Resistance	11.03 Ω at 25°C
Run Winding Resistance	5.15 Ω at 25°C
Locked Rotor Amperage (LRA) 50Hz	21 A
Rated Load Amperage (LMBP) at 50 Hz	4.3 A

MECHANICAL DATA

Displacement	16.8 cm³
Oil Charge	350 ml
Oil Type	ESTER
Oil Viscosity	ISO22
Weight	11.6 Kg

ELECTRICAL COMPONENTS

Start Capacitor	88-108 µf/330 V
Run Capacitor	15.0 µf/400 V
CSR CSIR BOX	Yes
Starting Device Description	RVA6M3C-114
Overload Protection	MSP18LJ-3261

EXTERNAL CHARACTERISTICS

Base Plate	SMALL
Tray Holder	NO

Connector	Internal Diameter	Shape	Material
Suction	8.1 mm	SLANTED 42°	COPPER
Discharge	6.1 mm	STRAIGHT	COPPER
Process	6.1 mm	SLANTED 42°	COPPER

PERFORMANCE

TESTED CONDITIONS

Tested Refrigerant	R-404A
Tested Application	LBP
Tested Standard	EN12900
Tested Cooling	Fan
Tested Voltage	220 V
Tested Frequency	50 Hz
Refrigerant Temperature	Dew

RATED POINTS

Condensing Temperature °C	Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
40	-35	478	1.1	435	-	12.96
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.						

PERFORMANCE CURVE

Condensing Temperature 35°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-40	396	1.07	370	-	10.06
-35	525	1.24	424	-	13.40
-30	686	1.42	484	-	17.58
-25	878	1.60	549	-	22.61
-20	1100	1.79	616	-	28.52
-15	1353	1.98	684	-	35.34
-10	1635	2.18	751	-	43.09
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					

PERFORMANCE CURVE

Condensing Temperature 45°C


Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-40	323	0.84	384	-	9.31
-35	431	0.97	443	-	12.46
-30	566	1.11	511	-	16.44
-25	727	1.24	587	-	21.28
-20	916	1.37	670	-	26.98
-15	1130	1.49	757	-	33.59
-10	1369	1.62	847	-	41.12
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					

PERFORMANCE CURVE

Condensing Temperature 55°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-30	442	0.85	521	-	15.09
-25	572	0.95	606	-	19.68
-20	725	1.03	701	-	25.14
-15	899	1.12	804	-	31.49
-10	1094	1.20	914	-	38.76
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					

ENVELOPE



EXTERNAL DIMENSIONS

